


LETW-S Electric 2 Speed Straight Torque Gun



- Supply : 220-230V AC, 50/60Hz
- Preset torque and automatic shutoff when the set torque value has been reached
- High output with an accuracy of $\pm 5\%$ and consistency of $\pm 3\%$
- Single-chip intelligent torque control system with LCD display
- Has manual 2-speed gearbox, high/low speed can be selected easily
- Free connection of power handle & drive unit
- Reliable continuous working rating suitable for production assembly line, installation work and maintenance jobs
- Double insulation design for greater safety

Description	Torque (Nm)	SQD Size	D (mm)	L (mm)	E (mm)	SPEED (rpm)	WEIGHT (Kg)
LETW-08S	100~800	3/4"	65	420	205	30	5
LETW-12S	200~1600	1"	74	460	205	12.2	6.5
LETW-26S	400~2800	1"	78.5	480	205	6.3	8.2
LETW-38S	700~4200	1-1/2"	88	500	205	5.1	9.5
LETW-60S	1000~6000	1-1/2"	113	529	205	2.6	14.9
LETW-80S	1200~8000	1-1/2"	120	539	205	1.8	16.8
LETW-100S	2000~10000	1-1/2"	128	555	205	1.5	18.3
LETW-120S	3000~12000	1-1/2"	128	555	205	1.5	18.3

LETW-A Electric 2 Speed Angled Torque Gun



- Supply : 220-230V AC, 50/60Hz
- Accuracy $\pm 5\%$, Consistency $\pm 3\%$
- Noise Output Level 80dBA
- Single-chip intelligent torque control system with LCD display
- Adjustable Twin Speed motor
- Right Angled drive head design more suitable for a limited working space area
- Main Drive head 360Deg rotation

Description	Torque (Nm)	SQD Size	D (mm)	L (mm)	E (mm)	SPEED (rpm)	WEIGHT (Kg)
LETW-08A	100~800	3/4"	65	249		30	6.6
LETW-12A	200~1600	1"	74	297		12.2	8.1
LETW-26S	400~2800	1"	78.5	317		6.3	9.8
LETW-38A	700~4200	1-1/2"	88	337		5.1	11.4
LETW-60A	1000~6000	1-1/2"	113	366		2.6	16.5
LETW-80A	1200~8000	1-1/2"	120	376		1.8	18.4
LETW-100A	2000~10000	1-1/2"	128	395		1.5	20
LETW-120A	3000~12000	1-1/2"	128	395		1.5	20