

Single Acting Hollow Cylinders

LRCH-Series Single Acting Hollow Cylinder

Hollow plunger design allows for both pull and push forces, single acting spring return. Collar threads for easy fixturing.



Model No.	Capacity (T)	Lifting.H (mm)	Min.H (mm)	Cylinder Dia. (mm)	Oil capacity (cm³)	Hollow Dia. (mm)	Weight (kgs)
LRCH-120	12T	8	55	69	14	19.6	1.5
LRCH-121	12T	42	120	69	75	19.6	2.8
LRCH-123	12T	76	184	69	136	19.6	4.4
LRCH-202	20T	49	162	98	150	26.9	7.7
LRCH-206	20T	155	306	98	476	26.9	14.1
LRCH-302	30T	64	178	114	298	33.3	10.9
LRCH-306	30T	155	330	114	722	33.3	21.8
LRCH-603	60T	76	247	159	626	53.8	28.1
LRCH-606	60T	153	323	159	1259	53.8	35.4
LRCH-1003	100T	76	254	212	1011	79	63

LCLP-Series Short Pancake Locknut Cylinder

Extremely low height for use in confined areas.
Safety lock nut for mechanical load holding.
Overflow port functions as a stroke limiter.



Model No.	Capacity (T)	Lifting.H (mm)	Min.H (mm)	Cylinder Dia. (mm)	Oil capacity (cm³)	Weight (kgs)
LCLP-602	60T	50	125	140	432	15
LCLP-1002	100T	50	137	175	734	26
LCLP-1602	160T	45	148	220	1040	44
LCLP-2002	200T	45	155	245	1285	57
LCLP-2502	260T	45	159	275	1650	74
LCLP-4002	400T	45	178	350	2517	134
LCLP-5002	520T	45	192	400	3287	189