

LRSM & LRCS SERIES

Flat Low Height & Short Hydraulic Cylinders

LRSM-Series Flat Low Height Cylinder

Compact, flat design for use where other cylinders will not fit.
High capacity have handle for easy carrying.
Single acting with spring return.



Model No.	Capacity (T)	Lifting.H (mm)	Min.H (mm)	Cylinder Dia. (mm)	Oil capacity (cm³)	Piston Dia. (mm)	Weight (kgs)
LRSM-50	5T	6	32	58 ' 41	4	25.4	
LRSM-100	10T	12	42	82 ' 55	18	38.1	1.5
LRSM-200	20T	11	51	101 ' 76	32	50.8	3.2
LRSM-300	30T	13	58	117 ' 95	55	63.4	5
LRSM-500	50T	16	66	140 ' 114	99	69.8	7.5
LRSM-750	75T	16	79	165 ' 139	164	82.6	11.3
LRSM-1000	100T	16	85	178 ' 153	203	92.2	18
LRSM-1500	150T	16	100	215 ' 190	317	114.3	36

LRCS-Series Short Cylinder

Light weight low profile design for use in confined spaces.
Grooved plunger end with threaded holes for mounting tilt saddles.



Model No.	Capacity (T)	Lifting.H (mm)	Min.H (mm)	Cylinder Dia. (mm)	Oil capacity (cm³)	Piston Dia. (mm)	Weight (kgs)
LRCS-101	10T	38	88	70	55	38	4.1
LRCS-201	20T	45	98	92	127	50	5
LRCS-302	30T	62	117	101	255	65	6.8
LRCS-502	50T	60	112	124	381	70	10.9
LRCS-1002	100T	57	141	165	756	90	22.7
LRCS-1502	150T	51	162	205	1025	138	42.1