

LRC SERIES

Single Acting Hydraulic Cylinders

Single acting by a heavy duty spring return. Collar threads, plunger threads and base mounting holes enable easy fixturing (on most models).
Designed for use in all positions (Horizontal and Vertical).



Model No.	Capacity (T)	Lifting.H (mm)	Min.H (mm)	Cylinder Dia. (mm)	Oil capacity (cm ³)	Piston Dia. (mm)	Weight (kgs)
LRC-50	5T	16	41	38	10	25.4	1.0
LRC-51	5T	25	110	38	16	25.4	1.0
LRC-53	5T	76	165	38	50	25.4	1.5
LRC-55	5T	127	215	38	83	25.4	1.9
LRC-57	5T	177	273	38	115	25.4	2.4
LRC-59	5T	232	323	38	151	25.4	2.8
LRC-101	10T	26	89	57	38	38.1	1.8
LRC-102	10T	54	121	57	78	38.1	2.3
LRC-104	10T	105	171	57	151	38.1	3.3
LRC-106	10T	156	247	57	225	38.1	4.4
LRC-108	10T	203	298	57	292	38.1	5.4
LRC-1010	10T	257	349	57	370	38.1	6.4
LRC-1012	10T	304	400	57	441	38.1	6.8
LRC-1014	10T	356	450	57	516	38.1	8.2
LRC-151L	15T	25	124	69	51	41.4	3.3
LRC-152	15T	51	149	69	104	41.4	4.1
LRC-154	15T	101	200	69	207	41.4	5.0
LRC-156	15T	152	271	69	309	41.4	6.8
LRC-158	15T	203	322	69	412	41.4	8.2
LRC-1510	15T	254	373	69	516	41.4	9.5
LRC-1512	15T	305	423	69	619	41.4	10.9
LRC-1514	15T	356	474	69	723	41.4	11.8
LRC-251	25T	26	139	85	83	57.2	5.9
LRC-252	25T	50	165	85	169	57.2	6.4
LRC-254	25T	102	215	85	339	57.2	8.2
LRC-256	25T	158	273	85	528	57.2	10.0
LRC-258	25T	210	323	85	697	57.2	12.2
LRC-2510	25T	261	374	85	863	57.2	14.1
LRC-2512	25T	311	425	85	1033	57.2	16.3
LRC-2514	25T	362	476	85	1202	57.2	17.7
LRC-308	30T	209	387	101	880	57.2	18.1
LRC-502	50T	51	176	127	384	79.5	15.0
LRC-504	50T	101	227	127	727	79.5	19.1
LRC-506	50T	159	282	127	1134	79.5	23.1
LRC-5013	50T	337	460	127	2403	79.5	37.6
LRC-756	75T	156	285	146	1601	95.2	29.5
LRC-7513	75T	333	492	146	3427	95.2	59.0
LRC-1006	95T	168	357	177	2239	104.9	59.0
LRC-10010	95T	260	449	177	3466	104.9	72.6